

CBR TEST MACHINE CTM-02

STANDARD: BS 1377, 1924; EN 13286-47; ASTM D1883; AASHTO T193

The automatic CBR test machine CTM-02 is designed for laboratory CBR test to evaluate the strength of soil subgrades and base course materials (the particle size of the soil is less than 40mm). Servo motor control makes the test process more stable. And the 7-inch touch screen displays test parameters and data, making operation easier.

CBR mould needs to be ordered separately.

TECHNICAL SPECIFICATIONS

Maximum load	50 KN 0.001KN
Load speed Penetration rod	1-5 mm/min
Penetration rou	End diameter 50 mm
Test mould Displacement sensor	Dia. 152 mm x 177.8 mm
	0-25mm, division: 0.01mm, linearity: 0.3%
Dimensions Power	34 x 45 x 88 cm
Fowei	220V,50Hz,500W
Weight	Net weight 88kg, gross weight 105kg





CBR MOULDS AND ACCESSORIES

Manufactured from high quality, longlasting material and with regular maintenance will give years of satisfactory performance. (All of the following CBR moulds and accessories need to be ordered separately.)

ASTM STANDARD

34-T0090 CBR mould complete with collar and perforated base plate. Plated steel, 6 in. (152.4mm) dia. x 7 in.

(177.8mm) body height

34-T0091 Spacer disc with "T" handle. 515/16 in. dia. (150.8 mm) x 2.416 in. (61.4 mm) high

34-T0094 Annular surcharge weight, 2.27 kg

34-T0095 Slotted surcharge weight, 2.27 kg

34-T0098 Cutting edge34-T0097 Solid CBR base

34-T0099 Straight edge. 3x30x300 mm



BRITISH STANDARD

34-T0090/B CBR mould body with base plate, made from plated steel threaded on both ends. 152mm ID x

127mm high, 50mm high collar

34-T0091


34-T0090/BC CBR mould with three plugs collar

34-T0090/B6 "C" spanner. To mount and to dismount the collar from the mould body, 1kg

34-T0095/B Split surcharge weight (2 kg, 2.27 kg selectable)







34-T0099

EXPANSION (SWELL)
TEST APPARATUS

34-T0093 Dial gauge tripod34-T0092/A Aluminium swell plate34-T0092/B Brass swell plate







SINCE 2006

ZHUOZHOU TIANPENG INSTRUMENT MANUFACTURING CO., LTD. Website: www.testmould.com Tel:+86-312-3852880